

# THERM IT

THERM IT

## GTC Woven E glass tape

GTC is woven E glass tape, it is non-combustable and reaches its softening point at about 600 °C.  
The glass yarns of GTC are treated with a size to prevent filaments when used.  
GTC has high tensile strength, good resistance to chemicals and temperatures.



## What's it used for?

1. GTC has many industrial applications.
2. Finishing tape in electrical applications.
3. Fire barrier.
4. Thermal barrier.
5. GTC has good compatibility with most resin systems.

## Technical information.

Tensile strength (0.23mm)	45 N/ mm @ 20°C
Colour	White
Operating temperature	220°C
Maximum short term temp	600°C
Warp ends (0.23 mm)	10 / cm
Weft picks (0.23 mm)	9 / cm

## Standard format.

GTC is available from stock as :-

25 mm x 0.23 mm      50 mt rolls.

50 mm x 0.23 mm      50 mt rolls.

Other thicknesses and constructions are available please ask Therm It for details.

### THERM IT,

Syke Mill, Belthorn Road, Belthorn, Blackburn,  
Lancashire. BB1 2NN

Tel: +44 (0) 1254 694733      Fax: +44 (0) 1254 691521  
Email: [sales@thermit.co.uk](mailto:sales@thermit.co.uk)      Web: [www.thermit.co.uk](http://www.thermit.co.uk)

THERM IT is a trading name of SLEEVE IT LTD